




Reference insert  
 Inserto referencia  
 Wkładka znakownika recyklingu  
 Indicadores de reciclagem  
 Pion de recyclage



Mat. : INOX. 1.4034. Hardness: 51 ± 3 HRC. Maximum temperature at work: 150° C.

S	K	E	H	A	B	REF.	S	K	E	H	A	B	REF.
5,6	1,5	8	7	10	12	IR-1012-01 (PET)	9	2,4	12	9	16	16	IR-1616-01 (PET)
						IR-1012-02 (PE-HD)							IR-1616-02 (PE-HD)
						IR-1012-03 (PVC)							IR-1616-03 (PVC)
						IR-1012-04 (PE-LD)							IR-1616-04 (PE-LD)
						IR-1012-05 (PP)							IR-1616-05 (PP)
						IR-1012-06 (PS)							IR-1616-06 (PS)
						IR-1012-07							IR-1616-07
6,8	1,8	10		12		IR-1212-01 (PET)	11,5	3,2	16		20		IR-2016-01 (PET)
						IR-1212-02 (PE-HD)							IR-2016-02 (PE-HD)
						IR-1212-03 (PVC)							IR-2016-03 (PVC)
						IR-1212-04 (PE-LD)							IR-2016-04 (PE-LD)
						IR-1212-05 (PP)							IR-2016-05 (PP)
						IR-1212-06 (PS)							IR-2016-06 (PS)
						IR-1212-07							IR-2016-07

\* Indicate the desired model after the reference.  
 \* Indiquer le sigle demandé après la référence.  
 \* Indicar o modelo desejado depois da referência.  
 \* Indicar el modelo deseado después de la referencia.